

When using oxygen/acetylene and oxygen/LPG equipment, it is important that the hoses used to convey each gas from the regulators to the operating equipment are colour coded, are of good quality and meet the required standards. The twin hose offered by Tesuco®, meets (or exceeds) the requirements of AS 1335 and is manufactured to very high specifications, ensuring long service life



BULK HOSE ROLLS

100 Metre Lengths

Twin hose for oxygen/acetylene and oxygen/LPG is available in 100 metre rolls. This allows for customised lengths to be cut from the roll when required. By fitting approved hose connections, like those supplied by Tesuco®, a complete hose assembly can be made.

SPECIFICATIONS

Packaging type	Plastic wrapped
Dimensions Product only With packaging	(L) 100 m x (W) 23 mm x (H) 12 mm (H) 180 x (ø) 500 mm
Materials for construction	Cord braided rubber
Maximum working pressure	1,500 kPa
Markings	TESUCO Year of manufacturing Gas type Pressure Australian standard
Standard	AS 1335 "Hose and hose assemblies for welding, cutting and allied processes"
Warranty	1 Year (manufacturer's defect)
Country of origin	Taiwan



PART NO	GAS SERVICE	COLOUR	WEIGHT (kg)
GWTWOA	Oxygen Acetylene	Blue Red	26.19
GWTWOL	Oxygen LPG	Blue Orange	24.23

TWIN HOSE OXYGEN/ACETYLENE

5 mm Hose Sets

Tesuco® has a range of hose sets available for oxygen/acetylene applications. They are manufactured to AS 1335 including the strength tests for the end fittings.

SPECIFICATIONS

Packaging type	Shrink wrapped with label and barcode
Materials of construction	
Hose	Cord braided rubber
Fittings	Brass
Maximum working pressure	1,500 kPa
Gas service	Oxygen Acetylene
Colour	
Oxygen	Blue
Acetylene	Red
Markings	TESUCO Year of manufacturing Gas type Pressure Australian standard
Standard	AS 1335 "Hose and hose assemblies for welding, cutting and allied processes"
Inlet/outlet connections	
Oxygen	5/8-18 UNF RH female
Fuel gas	5/8-18 UNF LH female
Warranty	1 Year (manufacturer's defect)
Country of origin	Taiwan



PART NO	DIMENSIONS	WEIGHT (kg)
GWTWOA5	(L) 5 m x (W) 23 x (H) 12 mm	1.5
GWTWOA10	(L) 10 m x (W) 23 x (H) 12 mm	2.8
GWTWOA15	(L) 15 m x (W) 23 x (H) 12 mm	4.2
GWTWOA20	(L) 20 m x (W) 23 x (H) 12 mm	5.6

TWIN HOSE OXYGEN/LPG

5 mm Hose Sets

Tesuco® has a range of hose sets available for oxygen/LPG applications. They are manufactured to AS 1335 including the strength tests for the end fittings.

SPECIFICATIONS

Packaging type	Shrink wrapped with label and barcode
Materials of construction Hose Fittings	Cord braided rubber Brass
Maximum working pressure	1,500 kPa
Gas service	Oxygen LPG
Colour Oxygen Acetylene	Blue Orange
Markings	TESUCO Year of manufacturing Gas type Pressure Australian standard
Standard	AS 1335 "Hose and hose assemblies for welding, cutting and allied processes"
Inlet/outlet connections Oxygen LPG	5/8-18 UNF RH female 5/8-18 UNF LH female
Warranty	1 Year (manufacturer's defect)
Country of origin	Taiwan



PART NO	DIMENSIONS	WEIGHT (kg)
GWTWOL5	(L) 5 m x (W) 23 x (H) 12 mm	1.5
GWTWOL10	(L) 10 m x (W) 23 x (H) 12 mm	2.7
GWTWOL15	(L) 15 m x (W) 23 x (H) 12 mm	3.8
GWTWOL20	(L) 20 m x (W) 23 x (H) 12 mm	4.8

HOSE CONNECTION & JOINER

Display packed



GWHCI



GWLP265



GWLP240LH



GWLP112RH



GWHC34



GWHC35

PART NO	SIZE	DESCRIPTION	TYPE
GWLP112RH	5 mm	Right hand	LP112
GWLP240LH	5 mm	Left hand	LP240
GWLP265	5 mm		LP265
GWHCF	5 mm	Left hand	
GWHCI	5 mm	Right hand	
GWHCF10	10 mm	Left hand	
GWHCI10	10 mm	Right hand	
GWHC34		Right hand hose joiner	WB34
GWHC35		Left hand hose joiner	WB35



For bulk orders unpacked, please contact Tesuco®.



CRIMPING TOOL

Part No: A2100

The crimping tool is specifically designed for use with all 5 and 10 mm clips to secure the hose barb once inserted into the ends of the hose. The tool is robust and easy to use and makes this a very simple fixing method.