
Nitrogen Regulator

High Pressure, High Flow







NITROGEN 6,000 kPa REGULATOR

The same professional regulator proven over years in the HVAC-R segment, but now with a hand wheel tightening feature and supplied in a sturdy IP55 rated plastic storage case with a foam insert to keep the regulator safe from damage.

FEATURES

- Safety pressure gauges to AS 4706
- Side entry to suit all nitrogen cylinders
- Gauge protectors for added durability
- Safety relief valve to protect downstream equipment
- 63 mm Gauges for easy reading adjustment
- Dual scale kPa and psi to suit industry standards
- Inlet filter to protect the seat
- 1/4" SAE flare outlet
- 5/16" SAE flare adaptor for R410a systems

SPECIFICATIONS

RI1SNI60C 30.000 kPa Max. inlet pressure 6,000 kPa Max. outlet pressure 150 m³/h Max. flow rate Inlet connection Type 50 Outlet connection 1/4" SAE flare Outlet adaptor 5/8" SAE flare Country of origin Italy



Spare part available: IP55 rated regulator case Part No: OTIP55C



Brochure Number: BRO_IND_HVA_SLT_60C_V03

QUALITY GAS EQUIPMENT Phone +61 2 9737 9937 Email sales@tesuco.com.au Website tesuco.com.au

Nitrogen Regulator

Spare Parts & Other Products





| | PART NO | DESCRIPTION |
|----|------------|---|
| 1 | SPRGP63BL | Gauge protector |
| 2 | SPRRV900 | Safety relief valve |
| 3 | SPRGI300NI | Safety pressure gauge inlet pressure |
| 4 | SPRGI100NI | Safety pressure gauge outlet pressure |
| 5 | SPR01B1F | 1/4" SAE flare outlet |
| 6 | SPRA410A | 5/16" SAE flare adaptor |
| 7 | SPRKI60 | Spare parts kit |
| 8 | SPR050 | Type 50 O-ring |
| 9 | SPRGWA | Gauge washer – aluminum Note: This part is inside the regulator but it is important to use this washer when replacing the pressure gauges. |
| 10 | SPRCKNI | Control knob, nut, label |
| 11 | SPRIH50B | Handwheel, Type 50 |
| 12 | SPRS50B2L | Regulator stem brass, Type 50 |



Brochure Number: BRO_IND_HVA_SLT_60C_V02

QUALITY GAS EQUIPMENT Phone +61 2 9737 9937 Email sales@tesuco.com.au Website tesuco.com.au