

# Disposable Nitrogen Gas Cylinders

For use in Air Conditioning, Refrigeration, Plumbing, Laboratory, Beverage & Food Packaging



## Save on cylinder rental! Portable and easy to use

In many cases, disposable cylinders are cheaper than refilling reusable cylinders. Non-refillable cylinders often save time and do not require periodic re-certification.

The 2.2 litre disposable gas cylinders have a much larger capacity and are filled to a much higher pressure than conventional disposable cylinders currently available.

Cylinder and regulator combination is ideal for on-site testing, purging, drain clearing or inerting.

Disposable gas cylinders meet EN 12205-2001 / TPED 99/36, EN 15614-1, EN 1418, CE Compliant for the cylinders and CE Directive 2010/35/EU for the valve.

### SPECIFICATIONS

Packaging type	Cardboard carton of 6 cylinders
Materials of construction	
Cylinder	Welded steel
Valve	Brass
Valve Seal	PTFE
Operating temperature	-20°C to +60°C
Dimensions (mm)	
Carton of 6	(H) 365 x (W) 350 x (D) 240
Product only	(H) 314 x (Ø) 102
Outlet connection	M10 x 1
Gas volume	0.22 m <sup>3</sup>
Tare weight	1.72 kg
Purity (typical)	Minimum 99.995%
Pressure	10,000 kPa @ +20°C
Test pressure	14,500 kPa
Warranty	1 Year (manufacturer's defect)
Country of origin	Italy

Note: Cylinder is fitted with nitrogen 2 gauge regulator.  
Part No: RG1MNI15. Outlet Pressure: 0-1,500 kPa



HACCP Compliant

### DISPOSABLE GAS CYLINDERS

2.2 Litre

#### PART NO. DESCRIPTION

GTAR2	Argon
GTARC102	Argon/CO <sub>2</sub> (10%)
GTAROX2	Argon/O <sub>2</sub> (2%)
GTNIHY2	Hydrogen (5%) / Nitrogen (95%)
GTCD22	CO <sub>2</sub>
GTHE2	Helium



### NITROGEN

HVAC-R



#### SPECIFICATIONS

#### RG1MNI15

Inlet type	M10 x 1
Outlet type	1/4" SAE flare
Pressure gauge	2
Delivery pressure	0-1500 kPa

### CO<sub>2</sub>

Beverage Systems / Home Brew



#### SPECIFICATIONS

#### RIMCD4M10

Inlet type	M10 x 1
Outlet type	5/16" Push fit
Pressure gauge	2
Delivery pressure	0-400 kPa

### ARGON & ARGON MIXTURE

Welding



#### SPECIFICATIONS

#### OTMRIGP5

Inlet type	M10 x 1
Outlet type	5/8-18 UNF RH male
Pressure gauge	1 (flow gauge)
Flow rate	0-8 L/min

### NITROGEN

Wine Dispensing



#### SPECIFICATIONS

#### RIM2NIM10

Inlet type	M10 x 1
Outlet type	5/16" Push fit
Pressure gauge	2
Delivery pressure	0-30 kPa